

Touch POS

MODEL EXPLICATION

AO2A1X3xx

Operator Display

- A:7"LCD+membrane keyboard
- B:7"Touch LCD+membrane keyboard
- C:14" Infrared Touch LCD
- D:14" Resistive Touch LCD

Customer Display:

- 1:7" LCD
- 2:20*2 VFD
- 3:Full lattice VFD
- 4:65*264 LCD

Customer Display Installation Types

- Null: Embedded type
- S:Pillar type

Other codes

- Null: No other functions
- G:GPRS
- M:Magcard
- R:RFID
- S:IC Card
- WB:BT
- W:WIFI

Printer

- Null: Default 58mm thermal printer
- 3: 80mm thermal printer with cutter
- 4: Double printers



Customer Display



7"LCD+Keyboard



LCD or inserted advertisement paper is optional.



Communication Port

Exclusive Functions

- ※ ALL-IN-ONE Design: integrating with the touch screen or hotkeys(100*2), printer, LCD customer display, magnetic,Mifare,smart card reader, GPRS, WIFI, Bluetooth, Micro SD, etc., meeting multifarious commercial demands.
- ※ Interactive media, advertisement playing, improving the product image and increasing profits.
- ※ SAM card of the highest safety class, issuing RFID offline with high safety, realizing chain management, instead of the online mode with high costs.
- ※ Frantend sattware of retail, restaurant, entertainment, etc., able to visit remote database and build network.
- ※ 3" printer with cutter or double-printer (2*38mm) is optional, compliant with the fiscal laws.

Advanced Functions and Features

- ※ Optional PC Based or ARM Based, for different management demands.
- ※ 14" touch screen (infrared or resistive), 2*100 hotkeys, convenient for different demands.
- ※ Microphone embedded design, extendable to be VOIP, convenient for business management.
- ※ Double Ethernet ports, convenient for network or WIFI (802.11b/g) establishment.
- ※ Optional foot stool, able to adjust the machine's height and angle.
- ※ Optional 7" (800*480) TFT LCD, 2*20 characters VFD, and 65*264 full graphic display.

Software interface



Specification

Processor		Cotex-A8 600MHz
Memory		256MB RAM, extendable 512 MB
Storage		256MB flash memory, extendable 512 MB
Power Supply		DC 9V
OS Support		Windows CE6.0 & Linux
Display	Operator display	7"TFT color LCD ; 14"TFT color LCD
	Customer display	7"TFT LCD ; 65*264 dots LCD ; 2*20 VFD; 24*128 VFD
	Touch Funtion	Infrared Touchscreen(option resistive touch screen)
I/O Port	Serial Port	4external port
	LAN Port	2 external 10M/100M
	Keyboard Port	1 external PS/2
	Mouse Port	1 external PS/2
	USB Port	4 external ports USB2.0
Printer	Printer	2"/3"thermal printer; 58mm/80mm*50
	Printing speed	150mm/s; 250mm/s
Physical Dimension	Dimension(W*D*H in mm)	482.2*359.6*432.1mm
	Weight(N.W.in KG)	3.3kg
Peripheral devices	MSR	3 track magnetic reader
	M1 RF card	RFID reader mouldle
	Smart Card	Support contact IC card
	SD card	Support G*2G SD card

Dimension

