

## SPECIFICATIONS

Signal Inputs/Output	
Input DDC Signal	5 volts p-p (TTL)
Maximum Single Link Range	1920X1080p
Output Video	HDMI 1.2a
Operating Frequency	
Video Amplifier Bandwidth	1.65Gpbs/165MHz
Vertical Frequency Range	50/60Hz
Resolutions(HDTV)	
Interlaced(50&60Hz)	480i,576i,1080i
Progressive(50&60Hz)	480p,576p,720p,1080p
Mechanical	
Size of HDMI 4 Ports Splitter Amplifier (L-W-H)	270x180x40mm
Weight of HDMI 4 Ports Splitter Amplifier (Net)	1300g
Size of Receiver (L-W-H)	100x65x25.5MM
Weight of Receiver (Net)	385G
Warranty	
Limited Warranty	1 Year Parts and Labor
Environmental	
Operating Temperature	0°C to +70°C
Operating Humidity	10% to 85 % RH (no condensation)
Storage Temperature	-10°C to +80°C
Storage Humidity	5% to 90 % RH (no condensation)
Power Requirement	
Power Supply for HDMI 4 Ports Splitter Amplifier	5V DC@ 3A,15W
Power Supply for Receiver	5V DC@ 2A,5W
Regulatory Approvals	
Converter Unit	FCC,CE
Power Supply	CE,FCC
Accessories Adapter	
AC Power Adapter	US standard, UK standard and so on
User Manual	English Version