EPe358 PCI Express Card

PCIe Bus Eight Port Card



- **★**Suitable for industrial control
- ★Suitable for Windows 2000/XP/2003
- ★Suitable for Windows WIN7/WIN8/WIN10
- **★**Suitable for **Linux**

EPe358 Specification:

Serial Communication Controller:

*type: EXAR 17V358 compatible.

Hardware compatibility:

*PCIe bus slot.

Software compatibility:

- * Windows 2000/XP/2003.
- * Windows WIN7/WIN8/WIN10.
- * Linux.
- * Other operation system.

Dimension:

- *Epe358 card: 87 * 80 mm.
- *Epe358 model with standard PCIe bracket

System I/O & IRQ mapping:

- *Memory mapping assigned by PCI BIOS.
- *one IRQ mapping assigned by PCI BIOS.

Port capability:

- *number of port: 8 ports per card.
- *Interface: RS232.
- *Baud Rate: each port can be configured to 50--115200bps.
- *Connector type: DB62 female connector.
- *R804 cable support DB62 male to eight DB9 male connector.
- *R801 cable support DB25M connector

Environment:

- *operating temperature : 0° C to 55° C
- *operating humidity: 10% to 95% RH
- *storage temperature : 0° C to 65° C
- *storage humidity: 5% to 95% RH

Performance upgrade capability and relative products:

- *A102 : PCIe card support two RS232 ports.
- *A104 : PCIe card support four RS232 ports.
- *A1016: PCIe card support 16 RS232 ports.
- *A2032 : PCIe card support 32 RS422/RS485 ports.
- *A3064 : PCIe card support 64 RS232/RS422/RS485 ports.
- *UTS040 box: USB to four ground isolated RS232 ports.
- *UTS004 box: USB to four ground isolated RS422/485 ports.
- *UTS485 box: USB to two RS232 and two ground isolated RS422/485 ports.
- *APORT040 box: IP to four ground isolated RS232 ports.
- *APORT202 box: IP to two RS232 and two ground isolated RS422/485 ports.
 - ***All names are the trademarks of their respective organization.

RAYON TECHNOLOGY CO., LTD.



2F, No. 177, Chung Shan 2 Rd., Lu Chou city, Taipei Hsien, Taiwan.

TEL: 886-2-82858362 FAX: 886-2-82857065 E-Mail: rayon@ms1.hinet.net; info@rayontech.com.tw

WEB: http://www.rayontech.com.tw