



**IP Phone SC-2002; SC-2002PE with 2 SIP, 3 way
conference call, full duplex speaker phone,
PoE option, Head set jack, XML, 1WAN, 1LAN**



Product Features:

- HD voice
- Support HTTP/TFTP/Telnet/Phone setting
- Enterprise addresses book.
- Private phone book application.
- Support Headset interface
- Suitable for call center applications.
- Support POE and AC adapter power supply
- Support HTTP/TFTP/FTP Auto-provision/TR069 for upgrade software

Technical Features:

Screen	Gray scale LCD with background light
	128*32 character
Language	Support Multi-Module
Line	2
Function Keys	6 Navigation keys (Arrow button, OK button, C button) Volume button (multiplex up and down keys) Hands-free, Mute, Headset, Message, Menu, Hold, Redial, Conference, Transfer
VoIP Protocol	SIP 2.0
Network Protocol	HTTP, BOOTP, FTP, TFTP, IEEE 802.1Q, *IEEE 802.1X
Codec	G.723.1, G.729 A/B, G.711 A/U, G.722

QoS	TOS, Jiffer Buffer, VAD, CNG, G.168 (32ms)
Network	2xRJ-45 10/100M Ethernet Interfaces (LAN/PC) IP Assignment: static IP, DHCP, PPPoE DNS Client, VPN (L2TP), VLAN/QoS
Speech	HD Voice: HD Codec/Handset/Speaker(Full-duplex) Handle, Headset and Hands-free model available Support call centre by headsets Separated 9 Level Volume Adjustment
Call Processing	Always Forward, Busy Forward, No-answer Forward Hotline line (Immediately/Delay) Call Waiting, Call Queuing Call Forward, Call Transfer, Call Holding, Call Pickup, *Callback Redial Phone directory speed dial, Call record direct dial 3-way conference DnD, *Blacklist, SMS Voice mail, Voice Prompt, Voice Message
Application	Enterprise phone directory XML Phonebook Private phone directory
Security	Login the website by password Signaling encryption Media encryption

Management	Upgrade: HTTP/TFTP/FTP Auto-provision/TR069 Configurations: Phone/Http/Auto provision/TR069 Debug: Telnet/Phone/Web
Power Supply	Power adapter: AC100~240V input and DC 5V/1A output PoE (IEEE 802.af)
Specification	Storage Temperature: 0°C ~ 60°C Operating Humidity: 10%~90% Size: 335mm*219mm*68mm Net weight: 1.07kg
Package	Qty/CTN: 10 PCS N.W/CTN: 10.7kg G.W/CTN: 11.2kg Measurement: 0.055CBM Carton Measurement: 460mm*350mm*355mm

SunComm TECHNOLOGY CO., LTD

7F, No. 53, Jian-Kang Rd., Zhong-he Dist., New Taipei City, Taiwan 23586 www.suncomm.com.tw

www.3GFixedWirelessTerminal.com

China : Shenzhen City: www.suncomm.cn www.suncomm-Shenzhen.com

Tel: 886-2-3234 1496 Fax: 886-2-3234 1393 E-mail: sales2@suncomm.com.tw