

Portable Wireless Ticket Micro-Printer

MODEL EXPLICATION

PP86Pxxxxxxxx

6: 76mm/80mm adjustable thermal printer
T: Desktop
P: Portable Printer

E: Ethernet
U: Slave (USB)
3: RS232
W2: 2.4G P-tooth
W4: 433MHz
WB: BT
IR: IrDA



Unique Functions

- ※RF2.4G/RF433MHz applies Aclas' patent CSMA power-saving protocol, which is able to establish many-to-many communication, and only 100uA power consumption in idle status.
- ※Water-proof Design. The rubber sticker in the paper outlet is able to prevent from water, oil. This greatly improves the reliability when the printer is used in polluted or greasy area, especially in the kitchen.
- ※With black mark sensor, able to provide black mark bill orientation printing, and support both right and left side detecting.



Advanced functions and characteristics

- ※Multi-optional wireless communication function: RF2.4G P-tooth, RF433MHz, BT, and IRDA.
- ※Powered by inbuilt 3.7V 2800mAh Li-battery (the inner voltage raised to 7V to supply power to the printer) makes the externality dexterous and no memory effects, which support a longer life than that of 2 pieces dry-battery. It is suitable for mobile police, mobile meter reading, and administration charging, etc. With excellent potable function, you can take with hanging on your waist, and match with your Handy Terminal makes up of travel sale group (able to print about 300 pieces of receipt).
- ※Optional wired communication function: RS232 port/USB port/Ethernet port, which supports graphic printing.
- ※Optional wired and wireless communication port for desktop POS printer, in which wireless communication port is able to eliminate wire clutter on desk and realizes POS periphery wireless collocation.
- ※New developed translucency upper cover, which is easy to control the usage of paper roll.
- ※With easy loading paper installation, no worry about paper jam.
- ※Support ESC/P command collection, and provide Windows drivers.
- ※Dustproof and waterproof crust is up to IP54. it is an ideal device for outdoor use.


Technical Specification

Working temperature	0°C~40°C
Working Humidity	5%~93%R.H. (Non-condensing)
Paper width	79.5±0.4mm
effective printing width	72mm
Printing density	203dpi
Printing Speed	75mm/s(Portable/Desktop)
Print font	12*24 dots English letters, 24*24 dots Chinese characters
Signal output	wireless:IRDA/ BT/ RF433MHz/ RF2.4G
	wired:RS-232, *USB, * Ethernet
Interface	RS232, *USB, *Ethernet
IrDA interface	IrDA port accord with IrDACOMM protocol and IrDA Ver1.2 orginal protocol
Data receiving buffer	32K
Power supply	DC7V 2A
Weight	370g without paper roll

Dimensions



Portable



Hang on the wall

